



1. MOW CURB WITH MEDIUM BROOM FINISH
2. FINISH GRADE - REFER TO NOTE # C
3. # 3 REBAR CONTINUOUS WITH 18-INCH LAPS MIN.
4. 1/2-INCH RADIUS TOOLED EDGES
5. CONTROL JOINT - REFER TO NOTE A BELOW
6. 90% COMPACTED SUBGRADE

**SECTION
NO SCALE**

NOTES:

- A. WEAKENED PLANE JOINT - 10 FEET O.C. MAXIMUM. CUT CONCRETE WITH TROWEL EDGE TO DEPTH OF REBAR. TOOL FINISH JOINT USING GROOVER WITH 1.5-INCH DEEP BIT.
- B. ISOLATION / EXPANSION JOINT - PLACE AT ENDS OF MOW CURB ABUTTING OTHER IMPROVEMENTS (TYP.).
- C. FINISH GRADE SHALL BE 1-INCH IN LAWN AREAS AND 3 INCHES IN PLANTING AREAS (BELOW TOP OF MOW CURB).
- D. CONCRETE SHALL BE CLASS 560-C-3250

APPROVED BY:

Jonathan George Smith

4/24/15

DIRECTOR OF PUBLIC WORKS
JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**CONCRETE
MOW CURB**

REVISION	BY:	APPROVED	DATE

STANDARD PLAN NO. 1301.02 SHEET 1 OF 1