



- 1. 1 1/2-INCH X 5 1/2-INCH PVC RAILS ATTACHED TO POSTS, ROUTE RAIL SLOTS ON POSTS AS REQUIRED TO ALLOW FOR ELEVATION CHANGES BETWEEN POSTS.
- 2. PVC POST CAP. GLUE AND ATTACH TO POSTS WITH STAINLESS STEEL SCREWS ON ALL SIDES
- 3. 5-INCH X 5-INCH MIN. SQUARE PVC POST
- 4. FINISH SURFACE
- 5. CONCRETE FOOTING, PROVIDE 1/2-INCH CROWN ABOVE FINISH GRADE
- 6. CONCRETE MOW CURB

**SECTION**  
**NO SCALE**

NOTES:

- A. OMIT FENCING WITHIN SIGHT DISTANCE RESTRICTED ZONES.
- B. WHERE PVC FENCING IS ADJACENT TO TRAIL, TURF, OR PROJECT BOUNDARY, INSTALL CONCRETE MOW CURB ALONG FENCE LINE.
- C. FENCING MANUFACTURER, COLOR, AND TEXTURE SHALL BE REVIEWED / APPROVED BY CITY.
- D. CONCRETE SHALL BE CLASS 560-C-3250.

APPROVED BY:

*Jonathan George Smith*

4/24/15

DIRECTOR OF PUBLIC WORKS  
JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**PVC FENCING**  
**SIDE VIEW**  
**(2-RAIL)**

REVISION	BY:	APPROVED	DATE