



- 1. 1-3/8-INCH MIN. ROUND TUBULAR STEEL
- 2. STANDARD METAL POST CAP
- 3. 2-INCH MIN. SQUARE POST / 14 GAUGE
- 4. 3/4-INCH MIN. SQUARE PICKETS / 16 GAUGE
- 5. 6-INCH X 8-INCH CONCRETE MOW CURB
- 6. 1 1/8-INCH MIN. TUBULAR STEEL RAIL ABOVE MOW CURB
- 7. 2500 PSI CONCRETE FOOTING - 8-INCH DIA. X 30 INCHES DEEP
- 8. 2-INCH X 2-INCH POST
- 9. CAULK JOINT W/CLEAR SILICON
- 10. FENCE RAIL SLIPS OVER POST ASSEMBLY

NOTES:

- A. ALL PANELS AND POST SHALL BE BLACK POWDER COATED. ALL WELDS FOR GATE HINGES MUST HAVE ONE COAT EPOXY PRIMER & TWO COATS OF EXTERNAL ENAMEL.
- B. TOP OF FOOTING SHALL BE AT ELEVATION TO ACCOMMODATE 6-INCH DEEP FORM BOARDS AND CONCRETE MOW CURB TO BE POURED AFTER FOOTING AND POST INSTALLATION ALONG FENCING.
- C. VERTICAL PICKETS SHALL BE AT 4-1/2-INCHES O.C. 2-INCH MAX. OPENING WHEN USED AT DOG PARKS.
- D. BOTTOM RAIL TO BE 4 INCHES FROM TOP OF MOW CURB. BOTTOM RAIL TO BE 2 INCHES FOR DOG PARKS.

APPROVED BY:

*Jonathan George Smith*

4/24/15

DIRECTOR OF PUBLIC WORKS  
JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**TUBULAR STEEL  
FENCE**

REVISION	BY:	APPROVED	DATE