



**PLAN
NO SCALE**

- 1. CMU WALL - SEE NOTE A
- 2. HEAVY DUTY GATE HINGE (3)
- 3. 3-INCH GALVANIZED STEEL ANGLE FRAME
- 4. MINI-V-BEAM 26 GAUGE WITH ENDURA CLAD FINISH AS MANUFACTURED BY ASC PACIFIC INC. OR APPROVED EQUAL. SPOT WELD TO ANGLE FRAME (CONTRACTOR TO SUBMIT SHOP DRAWINGS)
- 5. GALV. STEEL DIAGONAL CROSS BRACE
- 6. GALVANIZED STEEL STOP PLATE
- 7. CONCRETE FOOTING (18-INCH DIA. X 48-INCH DEPTH) / REFER TO STRUCTURAL ENGINEER'S SPECIFICATIONS FOR REINFORCEMENT
- 8. 4-INCH X 4-INCH TUBULAR STEEL GATE POST. SET POST FLUSH TO WALL, GROUT FILL POST SOLID. PAINT WITH (2) COATS ZINC PRIMER & (2) COATS SATIN FINISH PAINT - COLOR TO BE SELECTED
- 9. CONCRETE FLOOR
- 10. CONCRETE CURB

NOTES:
 A. 8-INCH X 8-INCH X 16-INCH CMU / REFER TO STRUCTURAL ENGINEER'S SPECIFICATIONS FOR REINFORCEMENT.
 B. CONCRETE FOOTING TO ACHIEVE 4300 PSI @ 28 DAYS.

APPROVED BY:

Jonathan G. Smith

4/24/15 DATE

DIRECTOR OF PUBLIC WORKS
 JONATHAN GEORGE SMITH

REVISION	BY:	APPROVED	DATE



CITY OF MENIFEE

**TRASH ENCLOSURE
 DOOR ENLARGEMENT**

STANDARD PLAN NO. 1301.14 SHEET 1 OF 1