



1. TREE BASIN PER SPECS.
2. TREE ROOTBALL TYP. (1-INCH MIN. ABOVE FINISH GRADE)
3. 4-INCH FLAT DRAIN CAP WITH VANDAL PROOF SCREW
4. FINISH GRADE
5. PVC LATERAL PER SPECS.
6. TRIPLE SWING JOINT
7. ROOT WATER SYSTEM (RWS) - PLACE AT EDGE OF ROOTBALL
8. NATIVE SOIL COMPACTED TO ORIGINAL DENSITY
9. TREE STAKE PER PLANTING DETAILS.
10. MULCH PER SPECIFICATIONS
11. 12 INCHES MIN.

**SECTION
NO SCALE**

NOTES:

- A. ROOT WATERING SYSTEMS SHALL ONLY BE USED WHEN POINT TO POINT IRRIGATION IS NOT USED.
- B. PROVIDE TWO RWS PER TREE WITH 1 GPM BUBBLER EACH.
- C. PROVIDE PERFORATED PVC PIPE IN ADDITION TO RWS.
- D. CLEAR MULCH 6 INCHES MIN. FROM TREE TRUNKS (TYP.)

APPROVED BY:

Jonathan S. Li

4/24/15

DIRECTOR OF PUBLIC WORKS
JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**TREE ROOT
BUBBLER**

REVISION	BY:	APPROVED	DATE
1	G.H.	J.S.	1/15/16

STANDARD PLAN NO. 1302.31 SHEET 1 OF 1