



1. LINE FLUSHING VALVE PLUMBED TO PVC AT LOW POINT / EACH END OF DRIP CIRCUIT
2. DRIPPERLINE SPACING PER PLAN / LEGEND
3. 1-INCH MAX. PVC EXHAUST HEADER - TYP.
4. PVC SUPPLY HEADER - TYP. / SIZE PER PLAN
5. DRIPPERLINE START CONNECTION - TYP.
6. DISC FILTER AND PRV (SEPARATE BOX AND ASSEMBLY, IF REQUIRED)
7. REMOTE CONTROL VALVE / LOW VOLUME
8. AREA PERIMETER / EDGE OF HARDSCAPE
9. DRIPPERLINE TUBING LATERAL
10. AIR/ VACUUM RELIEF VALVE AT HIGH POINT (AS REQ'D - REFER TO LEGEND)
11. PERIMETER LATERALS 2 INCHES TO 4 INCHES FROM EDGE

**PLAN  
NO SCALE**

NOTES:

- A. REFER TO LEGEND FOR DRIPPERLINE DESIGN PRESSURE AND MAXIMUM TUBING RUN.

APPROVED BY:

*Jonathan George Smith*

4/24/15

DIRECTOR OF PUBLIC WORKS  
JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**SUBSURFACE  
PIPE AND TUBING  
CENTER FED LAYOUT**

REVISION	BY:	APPROVED	DATE