



**PLAN  
NO SCALE**

- 1. UVR S X S X T TEE
- 2. UVR S X S X T TEE
- 3. UVR PVC LATERAL LINE
- 4. EPOXY COATED REBAR J-HOOK PER SPECS.
- 5. 1/2-INCH SALCO OR GPH TUBING RISER PER SPECS.
- 6. 9-INCH PVC COATED GALV. STAPLE
- 7. SALCO OR GPH RISER ASSEMBLY PER SPECS.
- 8. SALCO OR GPH 2 GPH EMITTER PER SPECS.

NOTES:  
 A. ALL PIPE AND FITTINGS SHALL BE PVC SCH. 40 UV-RESISTANT.  
 B. ALL PIPING SHALL BE BURIED 4 INCHES MIN.

PLANT SPACING	A	B	C	D
2' ON CENTER	18"	32"	42"	12"
3' ON CENTER	18"	42"	5'0"	12"
4' ON CENTER	24"	54"	7'0"	12"
5' ON CENTER	64"	64"	8'8"	12"

APPROVED BY:

*Jonathan George Smith*

4/24/15

DIRECTOR OF PUBLIC WORKS  
 JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**SHRUB EMITTER  
 ASSEMBLY LAYOUT**

REVISION	BY:	APPROVED	DATE