



1. 4-INCH ROUND DRAIN GRATE CAP, FLUSH WITH MULCH SURFACE
2. 3 TREE TIES, INSTALL AT END OF WIRES AT POINT OF CONTACT WITH TREE TRUNK, PLACE SEGMENT OF RUBBER HOSE OVER WIRE LOOP TO PROTECT TRUNK. INSTALL 1/2-INCH WHITE PVC PIPE OVER WIRE FOR VISUAL WARNING (SEE SPECS.)
3. DEADMAN ANCHOR FOR HOLDING GUY WIRE (REFER TO SPECIFICATIONS)
4. SET TOP OF ROOTBALL 2 INCHES ABOVE FINISH GRADE
5. 3-INCH DEPTH MULCH, PROVIDE 6-INCH CLEARANCE FROM TRUNK (REFER TO SPECIFICATIONS)
6. 6-INCH HIGH MIN. WATERING BERM (3-INCH HIGH BERM IN LAWN)
7. FINISH GRADE
8. PLANTING BACKFILL (REFER TO SPECIFICATIONS)
9. SLOPE PLANTING HOLE TO CORNERS WITH DRAIN PIPES
10. 4-INCH PVC SCH. 40 PERF. PIPE WRAPPED IN FILTER SOCK FILLED WITH 3/4-INCH CRUSHED ROCK (2 PER TREE)
11. 2 CU FT. OF 3/4-INCH CRUSHED ROCK (REFER TO SPECIFICATIONS) - 12-INCH DIA. X 24 INCHES DEEP SUMP BELOW ROOTBALL (2 PER TREE)
12. FERTILIZER TABLETS (REFER TO SPECIFICATIONS) - 8-INCH DEPTH MAX.

**SECTION
NO SCALE**

NOTES:

- A. SET ROOT BALL ON FIRM NATIVE SUBGRADE AT BOTTOM OF PLANTING PIT. SCARIFY SIDES AND BOTTOM OF PLANT PIT PRIOR TO BACKFILLING. SLOPE BOTTOM OF PIT TO PERFORATED PIPE.
- B. IN AREAS WITH HIGH WINDS, 3-INCH DIAMETER STAKES AND / OR V.I.T. TWIST BRACES MAY BE REQUIRED - REFER TO SPECIFICATIONS

APPROVED BY:

Jonathan G. Smith

4/24/15

DIRECTOR OF PUBLIC WORKS
JONATHAN GEORGE SMITH

DATE



CITY OF MENIFEE

**TREE GUYING
(48-INCH BOX TREES)**

REVISION	BY:	APPROVED	DATE
1	G.H.	J.S.	1/15/16

STANDARD PLAN NO. 1303.07 SHEET 1 OF 1